



**Pacific
Northwest**
NATIONAL LABORATORY


Leveraging Advanced Geophysics and Machine Learning to Support Soil and Groundwater Remediation at the Hanford Site

Tim Johnson, Jose Hernandez-Mejia, Glenn Hammond, Piyoosh Jaysaval, Jon Thomle, Anton Sinkov, Matt Taubman, Hilary Emerson, Rob Mackley




Motivation: Hanford 300 Area - In Situ Treatment of A Subsurface Uranium Source Zone

Plan view of 300 Area Treatment Site



Time-Lapse ERT Imaging of Amendment Delivery




300 Area Phase B Polyphosphate Injections

Challenges

1. ERT Images are qualitative and limited resolution
2. We cannot 'see' geochemical reactions / changes in mineral surface properties
3. Uncertainty Quantification

Solutions:

- 1) Can we generate a Digital Twin (or many) that honor the monitoring data (joint inversion)?
- 2) Field SIP Imaging?



E4D Time-lapse Images of Phosphate Injections

animation



Pacific Northwest
NATIONAL LABORATORY

Opportunities: Challenge 1


Emerging generative AI methods are addressing long-standing challenges in joint inversion.

- Assimilation of all available data = more accurate estimation of subsurface heterogeneity
- Generation of equally probably subsurface models, or 'digital twins' for uncertainty estimates.

Conditional Diffusion Model

output

input



“Generate a realistic image of a bovine tumbleweed stampede with cowboys on horses in Richland Washington”

How do conditional diffusion models work?

CDM Training

Training Image
+ description
(e.g. fluffy dog)

Forward Process: Iterative Noise Addition

Random Noise



<https://theaisummer.com/static/d007d60f773b61f4585cbec3869490d5/a878e/score-sde.png>

Inverse Process: Iterative Denoising

Random Noise
+ conditioning data
(e.g. fluffy dog)



CDM Objective

Given an image of random noise, generate an image that honors an input condition (i.e. fluffy dog).

*Image = PFLOTRAN digital twin
Input condition = Monitoring data*

Test Case: Hanford 100-K Area Soil Flushing Test

Hanford 100-KE Reactor Area





Flush Water Application




electrodes

100-K Area Geology and ERT Monitoring Images

Soil Flushing Setup




Time-lapse ERT Images



- 183-KE sodium dichromate tank
- 183-KE french drain and rail spur
- sodium dichromate pipelines
- infiltration zone boundary

Day.Hour=403.09

Change in Cond (Log₁₀ EC/E₀)



animation

Subsurface Properties

- Hydrogeologic, unsaturated flow, and petrophysical properties in each of the three units.
- Native pore water and flush water fluid conductivity
- Bounded by literature values
- 29 parameters total


Parameter	min value	max value
Hanford porosity	0.05	0.35
Hanford horizontal permeability [m ²]	2.00E-13	1.00E-07
Hanford vertical/horizontal permeability ratio	0.2	1
Hanford Archie's law cementation exponent	1.1	2.1
Hanford Archie's law saturation exponent	1.6	2.6
Hanford Archie's law tortuosity constant	0.8	1.2
Ringold unit porosity	0.2	0.5
Ringold horizontal permeability [m ²]	1.00E-12	1.00E-08
Ringold vertical/horizontal permeability ratio	0.2	1
Ringold Archie's law cementation exponent	1.1	2.1
Ringold Archie's law saturation exponent	1.6	2.6
Ringold Archie's law tortuosity constant	0.8	1.2
Pit porosity	0.05	0.35
Pit horizontal permeability [m ²]	2.00E-13	1.00E-07
Pit vertical/horizontal permeability ratio	0.2	1
Pit Archie's law cementation exponent	1.1	2.1
Pit Archie's law saturation exponent	1.6	2.6
Pit Archie's law tortuosity constant	0.8	1.2
Hanford and Pit VG-Alpha [1/m]	2.00E-05	0.009
Hanford and Pit VG-M	0.2	0.65
Hanford and Pit residual saturation	0.0055	0.24
Ringold VG-Alpha [1/m]	1.00E-05	0.008
Ringold VG-M	0.16	0.8
Ringold residual saturation	0.02	0.2
Hanford surface electrical conductivity [S/m]	1.00E-05	0.01
Ringold surface electrical conductivity [S/m]	1.00E-05	0.01
Pit surface electrical conductivity [S/m]	1.00E-05	0.01
Native pore water conductivity [S/m]	0.005	0.1
Flush water conductivity [S/m]	0.005	0.1

Training Data Generation









The CDM model self-trains by choosing which PFLOTRAN model to generate for examples.

Simulations are executed on high-performance computing systems.

Computationally demanding, but tractable



CDM digital twin generation performance: Raw ERT data matching



DT = Digital Twin
data values in ohm




Pacific Northwest
NATIONAL LABORATORY


How well do the digital twins predict soil flushing behavior?

- Twin 1 and Twin 2 honor the ERT data
- Disqualified twin does not
- Prediction performance based on # flush water pore volumes


True Model




Digital Twin 1



Digital Twin 2



Disqualified Twin






animation

Geophysical Imaging of Flow and Transport (GIFT) System


Objective:

- Calibration PFLOTRAN (Digital Twin) with CDM
- Use Digital Twin to design treatment delivery
- Assess delivery with ERT, monitor with SIP





GIFT Tracer Experiment Simulations / Training Data Generation


Material Properties



Tracer Simulations




Example Breakthrough Curves



Tracer Test #1 Time-Lapse ERT Imaging

ERT Imaging

- Injected @ 20 ml/min for 12 hours
- 1 hour between images
- Fast flow through coarse (16) sand
- Delayed flow through fine (70) sand
- Density driven flow
- Tracer transport along injection well annulus during injection



Animation


Field Scale SIP (FS-SIP) System

SIP Field Monitoring Challenges


- Electromagnetic Coupling
 - Cable coupling noise masks polarization responses
- Time Requirements
 - Up to days per image when low-frequencies are collected.



EM Isolation Cables



Control Unit






Pacific Northwest
NATIONAL LABORATORY

FS-SIP System Field Testing Image (Sept. 2025)

- 6 frequencies (1 mHz to 100 Hz) collected in 90 minutes.
- Excellent data quality
- Enables monitoring of amendment emplacement and post-emplaced geochemical reactions.

Static SIP Image Cross-Sections






Pacific Northwest
NATIONAL LABORATORY


Take Home Messages

- Subsurface digital twin generation advancements enabled by AI.
 - More informative and actionable use of ERT monitoring data.
- Advancements in field-scale SIP monitoring.
 - New instrumentation to enable ERT-like SIP monitoring.

Current: ERT Images



Future: Digital Twins





Thank you



REMPLEX
CENTER FOR THE REMEDIATION
OF COMPLEX SITES
@PNNL

Organized in cooperation with
 **IAEA**
International Atomic Energy Agency
Atoms for Peace and Development

RemPlex Global Summit

November 4–6, 2025

