

# Biological Treatment of Residual DNAPL

**Scott B. Wilson**  
President  
Regenesis

*In Situ Treatment of Groundwater Contaminated with Non-Aqueous Phase  
Liquids: Fundamentals and Case Studies*  
EPA TIO, EPA Region 5, ITRC  
12/12/2002

1



## **DNAPL as a Source of Contamination**


- **DNAPLs—Dense Non-Aqueous Phase Liquids**
  - **DNAPL sinks within aquifers to provide a long-term source of contamination**
  - **DNAPL dissolves into the aqueous phase to directly impact groundwater**
- **The presence of long-term source in the form of DNAPL (60% of NPL sites) is a major complicating factor in remediation**
  - **“accessibility” of DNAPL to pump and treat or chemical oxidation systems is limited**

2



# Residual DNAPL


(from: Friedrich Schuille (1988) Dense Chlorinated Solvents in Porous and Fractured Media. Lewis Publishers, Chelsea, MI)



3



## Bioremediation in Source Zones



$$\text{Remediation Time} = \frac{\text{Source Zone Mass}}{\text{Exiting Flux} \cdot (A)}$$

- **Exiting Flux Observed is a function**
  - velocity, dispersion
  - dissolution rate, partitioning

4



(J.B. Hughes, Civil and Environmental Engineering, Rice University)





## DNAPL Bioremediation

- **Microbial reductive dechlorination of dissolved phase contaminants increases dissolution and desorption of DNAPL/source zone contamination.**
- **A recent SERDP/ESTCP workshop identified *in situ* bioremediation as one of the two most promising source-zone treatment technologies (Stroo et al. (2002) article submitted to Env.Sci.&Tech.).**
- **Soil columns with actively dechlorinating microbes demonstrated 16x the PCE removal of abiotic columns (Cope and Hughes (2001) Env. Sci.&Tech., 35(10) p. 2014).**
- **Soil columns with biological substrates had 3x the DNAPL dissolution rate as no-substrate columns (Yang and McCarty (2002) Env.Sci.&Tech., 36(15) p. 3400).**

5



# Example of Biologically Enhanced Dissolution




6



(J.B. Hughes, Civil and Environmental Engineering, Rice University)



# Reductive Dechlorination can Decrease Source Longevity



- Dechlorination produces increasingly hydrophilic pollutants
- At equal mole fractions to PCE:
  - $[TCE]_{aq} = 9 \cdot [PCE]_{aq}$
  - $[DCE]_{aq} = 33 \cdot [PCE]_{aq}$
  - $[VC]_{aq} = 90 \cdot [PCE]_{aq}$
- DNAPL removal rate increased

7



(J.B. Hughes, Civil and Environmental Engineering, Rice University)




## **HRC and Desorption**

**A visible drop of TCE (about 0.5 grams) was placed in a flask. Water from a second flask containing soil and HRC was recirculated through the flask containing the pure TCE and its disappearance was monitored.**


8



**TCE Drop- Day 0**




**Day 5**



**Day 6**



**Day 12**



9



# Experimental Controlled Release System (ECRS)

- **ECRS is a simulated aquifer, a controlled field-scale system**
- **Rectangular experimentation tank (18 ft x 7 ft x 6 ft) packed with sand and fitted with stainless steel piping for sampling**
- **Controlled water flow (recycle or one-pass)**

10



(J.B. Hughes, Civil and Environmental Engineering, Rice University)



# ECRS Tank



11



RICE

(J.B. Hughes, Civil and Environmental Engineering, Rice University)



REGENESIS

## **Objective and Experimental Details**

**Evaluate the performance of Hydrogen Release Compound (HRC<sup>®</sup>) as an electron donor delivery system for source-zone bioremediation**

- **1L of PCE NAPL added to ECRS (day 0)**
- **lactate and acetate added to create initial anaerobic conditions (day 16)**
- **bioaugmentation (110 L of culture) because ECRS soil had low microbial activity (day 32)**
- **HRC (80 L) addition for long-term carbon and electron source (day 64)**


12



(J.B. Hughes, Civil and Environmental Engineering, Rice University)



# Plan View of ECRS Tank and Injection Points




13



(J.B. Hughes, Civil and Environmental Engineering, Rice University)



# Mole Fractions in Effluent



14



(J.B. Hughes, Civil and Environmental Engineering, Rice University)



## **Conclusions of ECRS Study**

- **PCE in the ECRS effluent was reduced by 90% after bioaugmentation and HRC addition.**
- **Further results (unpublished) indicate that HRC application in conjunction with bioaugmentation was the driver for removing greater than 90% of the DNAPL in 240 days.**

15




## **HRC<sup>®</sup> Performance in Tight Clays – Cookeville, TN**

- **HRC chosen as effective remediation technology with cost-saving benefits**
- **Goal was to degrade high concentrations of dissolved PCE and TCE in the presence of residual DNAPL at a tight clay site.**
- **Other motivations included: no interruption to facility operations, no lengthy maintenance and operations, and no construction of unsightly/obtrusive remedial systems**

16



# Well Locations and Site Map



17





**HRC warming before injection**



**HRC**

18



# HRC Field Application



**HRC is a viscous, injectable substance.**



**HRC is injected into the aquifer using direct-push technologies.**

19




## Results and Conclusions

- PCE at 110 mg/L and TCE as high as 200 mg/L were reduced, on average, 92%
- Daughter products such as cisDCE and VC have been detected and are decreasing with time
- Contaminant profiles (high concentrations of daughter products vs. PCE) suggest DNAPL is present
- The total mass of VOCs has been reduced > 86%
- A final injection of HRC is being considered for September 2002, site closure is expected in 2003

20




# Well TW-2 in Source Area



21



# Well PZ-2 in Source Area



22



# Oregon Department of Environmental Quality


Contact: Kevin Parrett

## Springdale Cleaners, Portland, OR

- Part of the State of Oregon Orphan Program
- PCE and daughter products present in groundwater
- Potential DNAPL and associated dissolved phase plume present
- Treated by accelerated natural attenuation with HRC-X™ and HRC®

23





24




**Aquifer Characteristics**

- Silty sand aquifer
- Depth to groundwater ranges from 2 - 7 ft bgs
- Groundwater flow direction is to the west
- Utility trench along shopping center causes local flow to the south
- Estimated groundwater velocity is 0.3 ft/day

**Contaminant Characteristics**

- PCE and daughter products present
- DNAPL likely present with an associated dissolved phase plume
- PCE ranges up to 120,000 ug/L near source area
- DNAPL adjacent to and beneath the building
- Adjacent utility trench appears to be conduit for DNAPL distribution perpendicular to flow




25



## Site Map Residual DNAPL Area

- Barrier application over 250 ft<sup>2</sup>
- 700 lb HRC-X™ (200,000 cP)
- PCE up to 120,000 ug/L
- Depth to water = 2 – 4.5 ft bgs
- Monitored JEMW-4 and JEMW-5



26



## **HRC-X™**

- **HRC-X is an extended release form of HRC that is used for treatment of residual DNAPL and source areas**
- **HRC-X is a high viscosity HRC (200,000 cP HRC-X vs. 20,000 cP HRC)**
- **HRC-X is a highly concentrated electron donor source with extreme longevity in the subsurface (3+ years)**

27



## HRC injection



28






29






30






### Residual DNAPL Area JEMW-4



32



**PCE Concentration Graph Comparing  
JEMW-4 and JEMW-5**



33



## Summary of Results for Springdale Site

- After 1.5 years, HRC-X™ reduced PCE mass by over 99% in both the residual DNAPL area and the dissolved phase plume.
- Project was very low cost: <\$20,000 in HRC and about 3 days direct push application (includes cost of treating dissolved-phase plume)

34



## Conclusions

- **Biodegradation can be used to accelerate and enhance residual DNAPL/source zone remediation**
- **HRC-X™ is designed to provide the longevity and high concentration electron donor necessary for DNAPL and source zone bioremediation**

35

